

**GENERATOR SPECIFICATION**

<b>Voltage</b>	230V - Earth/Neutral bond 115V - Centre Tap Earth (CTE)
<b>Phase</b>	1
<b>Frequency</b>	50Hz
<b>Prime Power (PRP)</b>	6.0 kVA / 4.8 kW
<b>Alternator</b>	NSM C100 SG
<b>Fuel tank capacity</b>	24.0 Litres
<b>Autonomy 75% load</b>	17.0 Hours
<b>LWA</b>	91
<b>dBA @ 7M</b>	66

**ENGINE SPECIFICATION**

<b>Engine</b>	Yanmar L100V
<b>Emissions certified</b>	EU Stage V
<b>Cylinders</b>	Single
<b>Distribution</b>	O.H.V.
<b>Aspiration</b>	Naturally aspirated
<b>Cooling</b>	Air
<b>Displacement</b>	0.435 Litres
<b>Rpm</b>	3000

**YANMAR**

3 Year Engine Warranty  
(Limited)

**DIMENSIONS (mm) & WEIGHT (KG)**

Status	Length	Width	Height	Weight
<b>Trolley Dry</b>	1270	785	890	193
<b>Trolley Wet</b>	1270	785	890	214
<b>Skid Dry</b>	980	640	890	180
<b>Skid Wet</b>	980	640	890	201

## CONTROL PANEL

- Key start complete with low oil pressure, high engine temperature, low fuel level & battery charge shutdown/warning lamps.
- MCB overload protection.
- RCD earth leakage protection - 230V output.
- AC voltage selector switch.
- 230V : 1 x 32A & 1 x 16A BS4343 sockets.
- 115V : 1 x 32A & 2 x 16A BS4343 sockets.
- Overload protection for each individual socket.
- Hours run meter.

## STANDARD FEATURES

- Industrial two wheeled trolley kit.
- Lifting eye.
- Self bleeding.
- 12V fuel lift pump.
- Gas strut canopy roof.
- Acoustic canopy complete with large access roof.
- Low oil pressure, high engine temperature & low fuel level shutdowns.

## POWER DEFINITION

**Prime Power (PRP)** : Applicable for supplying power to varying electrical load for unlimited hours in accordance with ISO 8528-1 under the agreed operating conditions with the maintenance intervals and procedures being carried out as prescribed by the manufacturers.

## OPTIONS

- Skid version available.
- Customised socket arrangement on request.
- AVR (Automatic Voltage Regulator).
- DSE 3110 start/stop control module - *see below for details*
- ATS Panel (Automatic Transfer Switch - DSE 3110 control module required).
- Air intake shutdown valve/Spark arrestor.
- Mains battery charger.
- Auto start/stop programmable 7-day timer (DSE 3110 control module required).
- DSE 4520 control module upgrade available.
- Telemetry remote communication available (DSE 4520 & DSE 890 required).

## DEEP SEA ELECTRONICS 3110 START/STOP CONTROL MODULE OPTION

- The module will display warnings, shutdowns & engine status information on the back-lit LCD screen.
- Engine shutdowns include, high engine temperature & low oil pressure, low fuel level warning.
- Monitoring & protecting AC volts & frequency (Hz).
- Hours run counter.
- Battery voltage monitoring.
- 2-wire remote start function.

