

Plunge Cut Saw SP6000

1 300 W • 2 000 − 5 800 min⁻¹ • 165 mm

Precise plunge cut circular saw

A precise plunge cut circular saw for accurate cutting. Ideal for installing furnishing or decking. Recommended for use with a guide rail. A motor capacity of 1 300 W and cutting capacity of 56mm. Speed can be adjusted between 2 000 – 5 800 min-1.



Technical specifications

Continuous Input Power 240V No load speed

Max. Cutting Depth at 90° Max. Cutting Depth at 48° Max. Cutting Depth at 45°

Blade Diameter

Bore Size (Arbor Diameter)

Power Supply Cord

Sound Power Level (L_{WA})

Sound Pressure Level (L_{pA})

Noise Uncertainty (K Factor) Weight Without Cable

Product Dimensions (L x W x H):

Max. Bevel Range (Right) Electronic brake

1300 W

2200 - 6400 min⁻¹

56 mm 38 mm 40 mm 165 mm 20 / 30 mm 4,0 m 103 dB(A)

95 dB(A)

3 dB(A) 4,1 kg

341 x 225 x 250

mm -1 - 48 °

User benefits

- Compatible with guide rail for more precise cuts
- Close-to-wall cutting; only 18 mm away from wall
- Precision accurate cutting delivers a splinter free mirror finish
- Electronic speed control maintains constant speed under load for smoother, higher quality cutting
- Easy to set depth adjustment with large scale
- Soft start minimises start-up shock and makes the tool start smoothly
- Ergonomic rubberised front grip and handle provide added comfort



EAN 0088381078115

Link to product - www.makitauk.com



Related products

Optional AC

165447-6

Parallel Guide

194385-5

Clamp set

198885-7

Guide rail joint connector set, 2 pcs

199826-6

Quick-Release Ratcheting Guide Rail

B-57613

Guide rail bag

E-12223

Circular Saw Blade, Efficut T.C.T, 165

— 194367-7

Guide rail, 3 000 mm

11A

196664-7

Bevel guide set

199140-0

Guide rail, 1 000 mm

1

783203-8

Hex Wrench 5 Mm

F-12217

Circular Saw Blade, Efficut T.C.T, 165



P-20177

Guide Rail Connector Set



Other

User manual

Parts drawing