

designed and created
for your needs



X-HYBRID MOBILE

6x150W LED - 8.5M

T-ZERO PRO



CO₂ of only 121kg per month



Run time before refuel:
minimum of 800hrs



Silent running time: 11hrs



6600 sqm bright, instant
LED light

For a more sustainable
and environmentally
friendly future

CAP
GROUP

HIRE SOLUTIONS



X-HYBRID MOBILE

6x150W LED - 8.5M

T-ZERO PRO



7 units per truck
Safe packaging and loading
allowing quick unloading

APPLICATIONS



Construction



Mining operation



Events



Military applications

FEATURES

- ✓ Multi-directionally adjustable and tiltable floodlights
- ✓ 7 section hydraulic vertical tower 8.5m, 340° rotatable
- ✓ Standard light sensor for auto start and stop
- ✓ Galvanised metalworks
- ✓ 80 µm powder coating
- ✓ Very compact dimension, up to 7 units per truck
- ✓ Central lifting eye, 4 sided forklift pockets for effective handling
- ✓ Plug & Play, colour coded cables and connectors
- ✓ Guided main coiled cable to avoid damage during tower operation
- ✓ Digital control panel and fuel level indicator
- ✓ Circuit breaker for electrical protection against overload
- ✓ External emergency stop button
- ✓ Fully bunded tank, 110%
- ✓ Certified wind stability up to 110 km/h
- ✓ 4 extendable & height adjustable stabilisers
- ✓ On board levels for guidance during stabilisation

Dimensions & Weight

Dimensions min (mm)	2944x1466x2570 (LxWxH)
Dimensions max (mm)	2944x2928x8500 (LxWxH)
Total weight (kg)	1290

Floodlights

Type	LED
Power (each)	150W
Floodlights number	6
IP level	67
Illuminated area (sqm)	6600

Mast

Lifting method	Hydraulic
Max Height	8.5 m
Max Wind Speed	110 km/h
Rotation	340°

Battery Pack

Type	AGM
Batteries number	4
Power Battery pack	24 Vdc 400 Ah
Expected battery cycle	500

Hybrid Mode

Running time from battery	11 h
Running time before refill	863 h
Charging time with LED's ON	11 h
Charging time with LED's OFF	8 h
Complete discharge recharge cycle	19 h
Hybrid mode consumption	0.23 l/h

Alternator

Model	Linz Alumen SB
Rated Output	3.5 KVA
Rated frequency	50 Hz
Voltage	230 V
Insulation class	H
Degree of Protection	IP 23

Engine

Model	Kubota Z482*
Fuel	Diesel
rpm	1500
Tank capacity (l)	222
Fuel consumption	0.55 L/h
Noise level dB(A) at 7 mt	0 - 62

* May vary based on stock availability. However, Yanmar primary equivalent brand eventually will be used



GAP Hire Solutions | www.gap-group.co.uk | 03330 094 153
Citypoint 2, 25 Tyndrum Street, Glasgow, G4 0JY

The company reserves the right to modify the technical specifications, items and design without notice. The images of the products are indicative for illustrative purposes only.